



0045639-1 02/26/90

7. A method, as recited in claim 6, further comprising:  
adding a corresponding entry to the *wset* coincident with recording of a lock  
owned in a write mode; and  
recomputing the *wset* by scanning the locks.

8. A method, as recited in claim 5, wherein the one or more conservative tests  
includes:

determining for each particular one of the delegator transactions, whether there  
are no delegatee transactions such that, for each type of conflict, a  
corresponding first set of transactions with which the delegatee can ignore  
conflicts is not a super-set of a second set of transactions that includes  
those transactions with which the particular delegator transaction can  
ignore conflicts of such type, excluding the delegator transactions  
themselves, and

if there is at least one write lock owned by at least one of the delegator  
transactions, then determining whether all delegatee can ignore conflicts  
with each other.

9. A method, as recited in claim 1, performed by a lock manager in a transaction  
processing system.

10. In a computational system wherein a value of a lock is encoded to identify (i)  
a set of one or more transactions that own the lock and (ii) respective one or more modes  
in which such transactions own the lock, and wherein at least some locks of equal value  
are represented using a same shared lock state, a method of validating bulk delegation of  
locks from one or more delegator transactions to one or more delegatee transactions, the  
method comprising:

for at least a subset of the bulk delegations, and for each shared lock state  
encoding having an associated owner set that includes at least one of the  
delegator transactions, testing validity of delegating a lock represented  
thereby based, at least in part, on ignore conflicts relationships amongst

the delegatee transactions and between the delegatee transactions and otherwise incompatible-mode owners that would remain after completion of the bulk delegation.

11. A method, as recited in claim 10, further comprising:

for each of the bulk delegations, performing one or more conservative validation tests and thereby obviating, for another subset of the bulk delegations, the validity testing for each shared lock state encoding.

12. A method, as recited in claim 11,

wherein the one or more conservative tests include testing for disjunction of a set of delegator transactions and a *wset*.

13. A method, as recited in claim 12, further comprising:

adding a corresponding entry to the *wset* coincident with recording of a lock value held in a write mode; and  
recomputing the *wset* upon each scan of the shared lock states.

14. A method, as recited in claim 11, wherein the one or more conservative tests includes:

determining for each particular one of the delegator transactions, whether there are no delegatee transactions such that, for each type of conflict, a corresponding first set of transactions with which the delegatee can ignore conflicts is not a super-set of a second set of transactions that includes those transactions with which the particular delegator transaction can ignore conflicts of such type, excluding the delegator transactions themselves, and

if there is at least one write lock owned by at least one of the delegator transactions, then determining whether all delegatee can ignore conflicts with each other.

15. A method, as recited in claim 10,  
wherein the shared lock states are at least partially encoded in an associative table  
of shared lock states (TSLs).

16. A method, as recited in claim 15,  
wherein at least a subset of the shared lock states that represent locks owned by a  
single owner is encoded separately from the table of shared lock states  
(TSLs).

17. A method, as recited in claim 15,  
wherein at least a frequently used subset of the shared lock states is encoded  
separately from the table of shared lock states (TSLs).

18. In a computational system wherein locks of identical value are represented as  
references to a shared lock state encoding of the value, a method of implementing a bulk  
delegation of locks from one or more delegator transactions to one or more delegatee  
transactions, the method comprising:

validating the bulk delegation based at least in part on ignore conflicts  
relationships amongst the delegatee transactions; and  
if validated, performing the bulk delegation.

19. The method of claim 18,  
wherein the performing of the bulk delegation includes, for each shared lock state  
encoding having an associated owner set that includes one of the delegator  
transactions, removing from the owner set each of the delegator  
transactions and adding thereto each of the delegatee transactions.

20. The method of claim 18,  
wherein the validating is based on ignore conflicts relationships amongst the  
delegatee transactions and between the delegatee transactions and

004-5639-1

21. The method of claim 18,  
wherein the validating is based on one or more conservative validation tests that,  
if successful, obviate validity testing for each shared lock state; and  
wherein, if not obviated by the one or more conservative validation tests, the  
validating includes, for each shared lock state encoding having an  
associated owner set that includes at least one of the delegator  
transactions, testing validity of delegating a lock represented thereby  
based, at least in part, on ignore conflicts relationships amongst the  
delegatee transactions and between the delegatee transactions and  
otherwise incompatible-mode owners that would remain after completion  
of the bulk delegation.

23. The transaction processing system of claim 22,  
wherein the transaction processing system implements a transaction model that  
supports a nested conflict serializability correctness criterion; and

24. The transaction processing system of claim 22, wherein as part of an initially-efficient, but conservative, validation, the lock manager:

- verifies that, for each delegator transaction and type of conflict between lock modes, a set of transactions with which a particular delegatee transaction can ignore conflicts is a super-set of the set of transactions with which the delegator transaction can ignore conflicts; and
- if at least one to-be-delegated lock is owned in a write mode by at least one of the delegator transactions, further verifies that each of the delegatee transactions can ignore conflicts with each other.

26. The lock manager of claim 25, embodied as software executable in an transaction processing environment that associates locking capabilities with transactions and that allows specification of certain conflicts between locking capabilities to be ignored.

- 36 -

28. The computer program product of claim 27,  
wherein, if the bulk delegation request is successfully validated, the bulk  
delegation is performed by the lock manager.

29. The computer program product of claim 27,  
wherein the one or more computer readable media are selected from the set of a  
disk, tape or other magnetic, optical or electronic storage medium and a  
network, wireline, wireless or other communications medium.

30. An apparatus comprising:  
means for representing plural locks having identical values using a single shared  
lock state encoding; and  
means for validating a bulk delegation of locks from one or more delegator  
transactions to one or more delegatee transactions based, at least in part,  
on ignore conflicts relationships amongst the delegatee transactions.

Add  $A^3$